

Matsushita Compressor and Motor J-Series Rotary Compressor Specification Table

Series			J						
Model			J32	J33	J35	J36	J39	J43	J47
Rated Output W			1,500.00	1,500.00	1,700.00	1,700.00	1,800.00	2,000.00	2,200.00
Displacement CC/rev			31.70	32.40	35.10	35.60	39.40	43.80	46.50
Cooling Capacity (Nominal)	60HZ	W	6,820.00	6,920.00	7,745.00	7,710.00	8,615.00	9,755.00	-
		(Kcal/h)	5,865.00	5,951.00	6,661.00	6,631.00	7,409.00	8,389.00	-
		(BTU)	23,273.00	23,614.00	26,430.00	26,310.00	29,399.00	33,289.00	-
	50HZ	W	5,560.00	(5,760.00)	6,105.00	5,990.00	6,800.00	7,610.00	(8,470.00)
		(Kcal/h)	4,782.00	(4,900.00)	5,250.00	5,151.00	5,848.00	6,545.00	(7,280.00)
		(BTU)	18,973.00	(19,400.00)	20,833.00	20,411.00	23,205.00	25,969.00	(28,800.00)
Weight Kg			22.60	21.70	22.60	21.60	23.20	24.30	15.90
Dimension (Nominal)	A	mm	271.00	271.00	271.00	271.20	286.20	286.00	310.00
	B	mm	127.00	126.50	126.50	126.50	126.50	134.00	134.00
	C	mm	315.00	320.00	315.00	323.80	323.80	331.00	394.00
	D	mm	15.90	15.90	15.90	15.90	15.90	15.90	15.90
	E	mm	9.70	9.70	9.70	9.70	9.70	9.70	9.70
	F	mm	75.00	75.00	75.00	75.00	75.00	89.10	89.10
	G	mm	46.70	51.70	46.70	51.70	51.70	48.20	72.20
UM: Under mass production									
UD: Under development (N-TEC () = Converted figure: JIS to N-TEC)									
Graphic View			Top View				Side View		
									